



Codice Code	Materiale Material	Durezza Hardness
724	HSS	Corpo/Body: 64±5 HRC Testa/Head: 50±5 HRC

Esempi di ordinazione / How to order:			
Cod.	d1	l1	R max 2
724	2	80	R

d1 h6	Progressione Gradation	l1 + 0,5 0	d2 0 - 0,2	k + 0,2 0	a	d3	r 0 - 0,2
2,0	0,1	71/ 80/ 100/ 110/ 120	3,0	3,0	1,0	d1 ±0,1	3,5
≥2,1	0,1		3,2	3,0	1,0	d1 ±0,1	3,5
≥2,3	0,1		3,5	3,0	1,0	d1 ±0,1	5,0
≥2,6	0,1		4,0	3,0	1,0	d1 ±0,1	6,5
≥3,0	0,1		4,5	3,0	1,0	d1 ±0,1	6,5
≥3,5	0,1		5,0	3,0	1,0	d1 ±0,1	8,0
≥4,0	0,1		5,5	4,0	1,5	d1 ±0,1	8,0
≥4,5	0,1		6,0	4,0	1,5	d1 ±0,1	8,0
≥5,0	0,1		7,0	4,0	1,5	d1 ±0,1	10,0
≥5,5	0,1		8,0	4,0	1,5	d1 ±0,1	10,0
6,0	0,5		9,0	4,0	1,5	d1 ±0,1	10,0
≥6,5	0,5		10,0	4,0	1,5	d1 ±0,1	12,0
≥7,5	0,5		11,0	4,0	1,5	d1 ±0,1	12,0
≥8,5	0,5		13,0	4,0	1,5	d1 ±0,2	15,0
9,5	0,5		14,0	4,0	1,5	d1 ±0,2	15,0
10,0	0,5		14,0	4,0	1,5	d1 ±0,2	15,0
10,5	0,5		15,0	4,0	1,5	d1 ±0,2	15,0
11,0	0,5		15,0	4,0	1,5	d1 ±0,2	15,0
11,5	0,5		16,0	4,0	1,5	d1 ±0,2	15,0
12,0	0,5		16,0	4,0	1,5	d1 ±0,2	15,0
13,0	1,0		17,0	4,0	1,5	d1 ±0,2	15,0
14,0	1,0		18,0	4,0	1,5	d1 ±0,2	15,0
15,0	1,0		19,0	4,0	1,5	d1 ±0,2	15,0
16,0	1,0		20,0	4,0	1,5	d1 ±0,2	15,0
17,0	1,0		21,0	4,0	1,5	d1 ±0,2	15,0
18,0	1,0		22,0	4,0	1,5	d1 ±0,2	15,0
19,0	1,0		23,0	4,0	1,5	d1 ±0,2	15,0
20,0	1,0		25,0	4,0	1,5	d1 ±0,2	15,0
22,0	1,0		27,0	4,0	1,5	d1 ±0,2	15,0
25,0	1,0		30,0	4,0	1,5	d1 ±0,2	15,0